

## **Economy Status Unit**

Part No. EP211



## Overview

- Designed to connect to the EP203 Automatic Extinguisher Panel to provide remote system status indication via three LEDs.
- Includes a mode (auto/manual) keyswitch.
- Mounts on a standard UK single gang 25mm flush or surface back box.
- Max. 8 economy status units per EP203 panel.

## **More Information**

## **Technical Specifications**

21-28VDC (100mA electronic fuse). Power requirements

Quiescent current 5mA. Auxiliary inputs

Indicators Release Imminent; Manual/Automatic operation; Manual Only operation.

Controls Operation keyswitch (Manual only or Manual & Auto).

Product dimensions (mm) 87 W x 87 H x 35 D mm. Can be mounted on a standard UK 25mm single gang flush or surface back box.

Construction & finish Plastic. IP Rating IP40. 86g

Operating conditions/temperature  $-5^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ . Max relative humidity: 95%.



T 01942 322744

F 01942 829867

E sales@c-tec.co.uk

W www.c-tec.com



















Network specification

Max. 8 EP211's per EP203 panel. Four wire connection (2 power, 2 data); Daisy-chain wiring. A 6K8 end of line resistor must be connected across the terminals of the last EP211 in the chain.

















