

Hush-Pro Detector Base

Part No. **HP408**



Overview

- Compatible with all Hush-Pro detectors.
- LPCB certified to the relevant parts of EN54 pending in conjunction with our Hush-Pro detectors.
- Easy to fit with lots of working space.
- Can be ceiling mounted in any orientation due to the true 360° degree viewing angle of the LED indicator strips on all Hush-Pro detectors.
- Integrated detector/base locking mechanism, head removal tool and ID tag.
- Simple 'click and twist' design.
- Remote LED terminals for the optional connection to a BF318 Remote indicator.
- Optional HP408R Hush-Pro relay base also available.



More Information

Technical Specifications

Approvals/certifications	Certified to the relevant parts of EN54 by the LPCB pending as part of our Hush-Pro fire detector certifications.
Compatibility	Compatible with all Hush-Pro fire detectors.
Supply wiring	2-wire monitored, polarity sensitive.
Connections	(1) +V In, analogue switch; (2) +V Out, analogue switch; (3) Remote LED +V; (4) 0V; (5) 0V; (6) Screen; (7) Screen. Terminals can accept up to 2.5mm cable.
Product dimensions (mm)	102.2mm diameter x 20.5mm deep.



Construction & finish	White polycarbonate rated to UL94 V-2 with bright tin plated steel terminals fitted with nickel plated steel screws/washers.
IP Rating	IP42.
Weight	55g.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom