

Hush-Pro Weatherproof Hi-Output Wall Sounder

Part No. **HP430A/DR/65**



Overview

- An IP55 rated weatherproof Hi-Output sounder designed for use with Hush-Pro domestic fire alarm systems.
- Certified to EN54-3 & 17 by the LPCB.
- Impressive 100dB(A) sound output @ 1m.
- 5.5mA alarm current.



More Information

Technical Specifications

Approvals/certifications	Certified to EN54-3 & 17 by the LPCB.
Protocol/compatibility	Compatible with C-TEC's HP508 Hush-Pro Controller.
Application/operation	Designed to be wall mounted. IP55 rated and suitable for use outdoors.
Flash rate & colour	0.5Hz / White.
Supply/operating voltage	27 to 40V DC.
Quiescent current	550µA.
Nominal SPL (Sound Pressure Level)	100dB(A) when set to tone 1.
Alarm current	5.5mA (Sounder on max).
Indicators	Polling (red LED).
Product dimensions (mm)	114mm diameter x 131mm deep.
IP Rating	IP55.



Weight 315g.
Operating conditions/temperature -10°C to +55°C. Max. 95% RH (Non-condensing).



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom