

Hush-Pro 92dB(A) Base Sounder

Part No. **HP431A/W**



HP431A/W pictured with BF330CTLIDW

Overview

- A high-quality base sounder with an impressive 92dB(A) sound output for use with C-TEC's HP508 Hush-Pro BS5839-6 Grade C Controller.
- Certified to EN54-3 & 17 by the LPCB.
- 460µA-5.5mA quiescent current.
- 5.5mA alarm current.
- White ceiling fixing plate & detector spur wires included for optional connection to a Hush-Pro detector/base allowing it to be used as part of stacked sounder/detector/base combination.
- Optional BF330CTLIDW white or BF330CTLIDR red cap available for stand-alone use.
- IP21C rated.
- Up to 16 field devices (detectors, sounders and/or I/O units) per Controller.



More Information

Technical Specifications

Approvals/certifications	Certified to EN54-3 & 17 by the LPCB.
Protocol/compatibility	Compatible with C-TEC's HP508 Hush-Pro Controller.
Application/operation	Designed to be ceiling mounted - either stand-alone with a red or white cap or as part of a stacked Sounder/Detector Base combination.
Supply/operating voltage	27 to 40V DC.
Quiescent current	460uA - 5.5mA @ 24V.



Nominal SPL (Sound Pressure Level)	92dB(A) on evacuation (Fire Level 2) tone. See notes for tone details.
Alarm current	5.5mA (Sounder on max).
Indicators	Polling (green LED) & Short Circuit Isolator Active (amber LED).
Product dimensions (mm)	122mm diameter x 46mm deep (not including optional CAST detector and base).
IP Rating	IP21C (Type A).
Weight	170g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).
Notes	Evacuation (Fire Level 2) tone: 610Hz for 0.5s, 810Hz for 0.5s. Local (Fire Level 1) tone: 500-1200Hz, slow whoop, for 3.5s on, 0.5s off.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom