

DataSheet

The home of innovation and elite performing PFAS-free fire extinguishers in the UK, CommanderEDGE boasts a number of reliable and extensively tested fire extinguishers. The range is fully Kitemarked by BSI and is the choice of the professional with its mix of performance, quality and value.

FOAM FIRE EXTINGUISHERS

Available in 3ltr, 6ltr and 9ltr units to support a range of applications and Class B risk settings, the new and improved CommanderEDGE enviroFoam Fluorine-Free Fire Extinguisher range has been designed and developed to support the ever-growing demand for a true eco-friendly foam firefighting solution.

On a Class B fire, it creates a layer of dense foam that rapidly forms a blanket on the surface of the fire. This cuts off the oxygen supply, quickly extinguishing the fire. The foam blanket also helps to cool the fire, further preventing reignition.

Technical Specification	FX-FFF-003-CCF	FX-FFF-006	FX-FFF-009
Capacity	3 litre	6 litre	9 litre
Fire Rating	13A 70B	27A 144B	34A 183B
Extinguishing Medium	Fluorine Free Foam	Fluorine Free Foam	Fluorine Free Foam
Working Pressure	15 bar @ 20°C	15 bar @ 20°C	15 bar @ 20°C
Temperature Range	0° to 60°C	0° to 60°C	0° to 60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen



PRODUCT CODE

FX-FFF-003-CCF | FX-FFF-006 | FX-FFF-009

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FX-FFF-003-CCF: 418 x 195 x 128
FX-FFF-006: 501 x 275 x 165
FX-FFF-009: 570 x 285 x 190

WEIGHT

FX-FFF-003-CCF: 5.2kg
FX-FFF-006: 9.52kg
FX-FFF-009: 14.2kg

- Kitemarked to BS EN3
- MER approved
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Plastic base skirt for protection
- Polyethylene internal lining
- 35kVa Dielectric test certified

 029 2086 8333

 029 2085 0627

 sales@checkfire.co.uk

 www.CheckFire.co.uk

