

# 9-30709

## AirSense Stratos Standalone Command Module

### Description

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

### Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Details

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

# 9-30709

## AirSense Stratos Standalone Command Module

### Technical specifications

#### General

|                   |             |
|-------------------|-------------|
| Status indication | LED and LCD |
| User interface    | Keypad      |

#### Electrical

|                     |                  |
|---------------------|------------------|
| Operating voltage   | 21.6 to 26.4 VDC |
| Current consumption | 250 mA           |

#### Output

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| Output quantity        | 5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c) |
| Output type and rating | 500 mA @ 30 V                                                 |

#### Physical

|                     |                               |
|---------------------|-------------------------------|
| Physical dimensions | 427 x 372 x 95 mm (W x H x D) |
| Net weight          | 5.2 kg                        |
| Colour              | Cream                         |
| Mounting type       | Wall mount                    |
| Cable entries       | 6 x M20                       |
| Material (body)     | Sheet steel                   |

#### Environmental

|                       |                        |
|-----------------------|------------------------|
| Operating temperature | -10 to +60°C (EN54-20) |
| Relative humidity     | 0 to 90% noncondensing |
| Environment           | Indoor                 |
| IP rating             | IP40                   |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [uk.firesecurityproducts.com](http://uk.firesecurityproducts.com) online or contact your sales representative.

Last updated on 18 February 2025 - 11:18