

Emergency Voice Communication System Mains Isolator Keyswitch

Part No. ECU326/WS



Overview

- Allows the mains to a SigTEL disabled refuge/fire telephone system controller to be switched on or off.
- Supplied with a surface mounting back box.
- Double pole and fitted with a 5A Fuse.
- Supplied with a special key that is only available to the responsible person.
- Can be wired with 1 x 2.5mm² or 2 x 1.5mm² cable to ensure only independent sole main supplies are used to the SigTEL controller.



More Information

Technical Specifications

Approvals/certifications	Third-party tested to the relevant insulation and isolation requirements of IEC/EN 60669.
Type	Double pole, lockable, 230V
Mains rated current	5A.
Supply/operating voltage	230 VDC.
Quiescent current	2mA if LED, 0mA if no LED,
IP Rating	IP30.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Construction & finish	White PVC.



Product dimensions (mm)	Switch Plate 86 x 86 mm x 25 or (25.7mm deep with LED), with supplied back box fitted 54mm deep.
Weight	TBC.
Notes	Key type: Red C-TEC S-Key.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom