



SERAGE

QUALITY RELIABILITY VISION



4 CHANNEL NVR



No.	Description	No.	Description
1	POWER SWITCH	7	ALARM IN/OUT
2	LINE IN	8	AUDIO OUT
3	USB PORT	9	VGA OUTPUT (MAIN)
4	LAN NETWORK	10	HDMI OUTPUT (MAIN)
5	PoE INPUTS	11	RESET BUTTON (10SEC)
6	48v DC POWER SUPPLY		


AI FEATURES:




License Plate Detection




Crowd Density



People counting



Pedestrian & Vehicle Detection



APP Notifications



Face Recognition



NDA (National Defense Authorization Act) compliant, refers to products that are "safe to use" by government agencies and enterprises.

SR8004NP

Resolution	8MP, 5MP, 3MP, 2MP (1080P) 1.3MP (960P), 1.0MP (720P)
Inputs	50Mbps
Out	64Mbps
Compression	Audio: G.711A;G.711U Video : H.264/H.264+/H.265/H.265+
Frame rate	4K:45fps 4MP:90fps 2MP:180fps
AI	Yes
Event	MD(Sensitivity Level 1~8)
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	Max 4CH playback
Fisheye	Use WEB CMS,device does not support
Local	UI5.0
WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above

Mobile App	SERAGE
Push Notification	Yes
Password Reset	Factory Reset Button: Press 10 seconds
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
HDMI	(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
POE	4*RJ45, 802.3at/af
Ethernet	1 RJ45 10/100 Base-T
USB	USB2.0*1(front) USB2.0*1+(rear)
Audio Out	1
HDD	1 SATA, up to 8TB
Alarm Input/out	4 in /1out
OSD Language	English/French/Spanish/Portuguese/German Italian/Greek/Danish/Finnish/Russia/Hebrew Turkish/Bulgarian/Arabic/Korean/Japanese Thai/Hindi/Romanian/Dutch/Polish
Dimension (WxDxH)	300x227x53mm
Rack Mount	Shelving required
Input Voltage/Current	DC48V/1.2A PoE Swith :48V
Power Consumption	5W
Operating Temperature	-10°C~+50°C (14°F ~ 122°F)
Humidity	Less than 90%RH