





















SRPDNC5FSAIW/B

Video

Imaging Device 1/2.7"

Effective Pixels5MP 2880 (H) x1620 (V)Scanning SystemProgressive CMOS

 $\begin{tabular}{ll} \begin{tabular}{ll} \beg$

B/W 0 lux @ IR ON

Lens Type

Focal Length (Zoom Ratio) 2.8 mm **Max. Aperture Ratio** F No. 1.0

Angular Field of View Horizontal:110°, Vertical:58°,

2m

Diagonal: 132°

Min. Object Distance

Lens Type Fixed(M12)

Operational

IR LED WarmLight

Red Blue Light 2 (1 Red&1 Blue)

IR Viewable Length 25m WarmLight Viewable Length 20m

Type of complementary light Hybrid (IR and Colour)

ATURES





WHERE

Residential, commercial and retail outlets, especially areas where its very dark at night and a clear colour picture is needed. Suitable for indoors and outdoor use

WHY

Whilst the camera can be viewed in colour 24/7, the camera can be set up on infra-red (IR) and turns to colour when motion is detected. It's great for deterrent purposes as the camera has flashing lights, a siren, and a built-in microphone and speaker, which allow users to listen or speak remotely via the app or web browser.



Operational

Motion Detection

Wide Dynamic Range **Digital Noise Reduction**

Image Setting

White Balance

Electronic Shutter Speed On-Board Storage

Audio **Custom Voice**

Hardware Reset

Smart Feature

Off/On (8 Level)

WDR

3D DNR

Full Colour Mode/Day&Night

Mode/Schedule

Auto/Manual 1/5 ~ 1/20000s

Micro SD slot, up to 256GB

Built-in microphone&Speaker

Yes

"Face Detection (FD, Human&Vehicle

Detection (PD&VD), Perimeter Intrusion Detection (PID), Line Crossing Detection (LCD), Cross Counting (CC), Stationary Object Detection (SOD), Heat Map (HM), Crowd Density Detection (CD), Queue Lenght Detection (QD), license Plate Detection (LPD),

Rare Sound Detection (RSD)"

Network

Ethernet

Video Compression Format

Resolution

RJ45(10/100BASE-T)

H.265/H.264

"Main Stream@30fps

720P(1280x720) Sub Stream@30fps

720P(1280x720),VGA(640x480),QVGA(

Mobile Stream@30fps

VGA(640x480), QVGA (320x240) "

Video Quality Ajustment Bitrate control method

Protocol

Security

Application Programming

Interface

Web Viewer

5MP(2880x1620),4MP(2560X1440) 3MP(2304x1296),1080P(1920x1080)

320x240)

256Kbps ~ 8Mbps

CBR/VBR

"TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/R

TSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP"

IP address filter; complicated

password; Authenticated username

and password

"IE10/11

Safari V12.1 above Firefox V.52 above

ONVIF(Profile S/G/T)

Google chrome V.57 above

Edge V.79 above"

Environmental

Operating Conditions Ingress Protection

-35~+60°C/less than ≤ 90% RH

IP67

Electrical

Input Voltage / Current

Power Consumption

D12V/POE(IEEE802.3af)

DC12V: max 5.8W; POE (48V):

max 7.1W

Mechanical

Material

Dimensions (HxWxD)


Weight


Metal

100*100*90mm

425g

Dimensions





ACCESSORIES (Optional)



SRVFDWB



SRBDPOEWB



