



# **12MP IP FISH EYE**















# SRPNF12MP

## Video

Resolution Image Sensor Min. Illumination 12mp 4000(H)×3000(V)
1/2.3" Progressive CMOS
Colour 0.01lux @ F1.6(AGC ON);
B/W 0 lux @ IR ON

1.6mm, Angle of view: 180°

# **Lens Type**

Shutter Lens F No. Day & Nig

F 2.0 ±5%

IR cut filter with auto switch

1/5 ~ 1/20000s

Day & Night

(Day/Night/Auto/Image/Schedule)

WDR

### Operational

Video Compression Video bit rate Triple Stream Frame Rate H.265/H.264/H.265+/H2.64+/MJPEG 256Kbps ~ 16Mbps

yes

Mainstream: 4000x3000, substream:

1280x960P

640\*480 Mobilestream:640\*480 Mainstream: 3000x3000 substream: 1080x1080,720x720,480x480

Mobilestream:480x480

Mainstream: 2560x2560 , substream: 1080x1080,720x720@,480x480

Mobilestream:480x480

Mainstream: 2160x2160 , substream:

# **EATURES**





# **WHERE**

Restaurants and bars, warehouses and retail outlets, classrooms and public spaces, elevators.

# WHY

Our 12MP fisheye camera offers 360-degree field of view, allowing you to monitor an entire room or area with a single camera. This reduces the need for multiple cameras and helps in covering blind spots. The fisheye image can be de-warped during live view and playback with up to 13 views.



Scan to watch the Fish eye Demo video.



# **Operational**

Frame Rate 1080x1080,720x720,480x480

Mobilestream:480x480

Mainstream: 1520x1520 , substream: 1080x1080,720x720,480x480

Mobilestream:480x480

Mainstream: 1080x1080, substream:

1080x1080,720x720,480x480

Mobilestream:480x480

Mainstream: 720x720, substream: 1080x1080,720x720,480x480

Mobilestream:480x480

BLC Support ROI Support

System Compatibility ONVIF( Profile S, G, T)

Led 3pcs (Smart Motion Detection)

IR Range Up to 10m

**SD storage** Micro SD slot, up to 256GB

Alarm Trigger Yes
Microphone Yes
Speaker Yes
Reset Button Yes

# Network

Protocols TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RT

SP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS

,FTP

Interface RJ45 10M / 100M

PoE Yes

# **Environmental**

Operating Temperature  $-35\sim$ +60°C

Protection IP 66

# Electrical

 Power Supply
 DC 12V/POE

 Consumption
 3.8 - 9.6W

# General

 Dimension
 Ø120\*55mm

 Weight
 appr 400g

## **Dimensions**





