


Remote WC Alarm Kit

ViAC-RTK-W



The AssistCall family of panels and devices are manufactured from white polycarbonate. They are designed to fit standard MK 25mm depth back boxes, double gang for the controller and single gang for the alarm plates. If using with a surface box specify curved corners.

- Fully compliant to BS 8300-2:2018
- Complete WC alarm kit
- Remote 1-Zone control module
- Onboard relay output
- Acknowledge function
- Monitored alarm input

Overview

The AssistCall System is a family of matching modules and devices that provide a complete alarm system compliant to BS 8300-2:2018.

Standalone applications

The ViAC-RTK-W Remote kit provides all the devices required for a single emergency assistance alarm system. It consists of a ViAC-1ZC-W -1 zone controller, ViAC-CPP-W pull cord, ViAC-CNP-W cancel button and a ViAC-ODP-W overdoor indicator.

Monitored Alarm

Although not mandatory, the alarm line is fully monitored for open and short circuits. This gives confidence that the alarm is wired correctly and intact.

Acknowledge function

BS 8300 requires audible and visual feedback such that when the alarm is activated the occupant is notified that not only has the alarm been received but is being actioned. This will alleviate distress that help is on the way. The unit can be positioned within a central location to notify staff or colleagues of activation.

Simple Installation

The system uses Cat5/Cat6, security cable or T&E/flex for the alarm circuits. For example: 2 core 1mm T&E, 2 core flex, 0.22mm security cable.

Integral PSU

The ViAC-1ZC has an integral mains power supply unit.

Simple relay outputs

The ViAC-1ZC has an onboard relay contact allowing it to signal off site or to connect to BMS etc.

Remote WC Alarm Kit

ViAC-RTK-W

Technical Specification

Details	ViAC-RTK-W
Power	
Integral Power	Mains into controller
Inputs	
Lines	1
Voltage	12 VDC Nominal
Monitoring	Open and Short Circuit
End of Line	10k Ω
Outputs	
Alarm Relay	1x Volt free NO, Com 24VDC 3A
Controls and Indications	
Accept button	1x Push Button (with alarm indication)
Statutory indicators	1x DC power/status indicator Lamp test feature

Details	ViAC-RTK-W	
Alarm Field Cabling		
Type	Cores	Distance from 1ZC
LSF flex/T&E	2 cores 1mm	500m
Cat5/6 or security	1× pair 0.22mm	50m
Cat5/6 or security	2× pair 0.22mm	100m
Standards Compliance		
EMC	EN 55035:2017+A11:2020 EN 55032:2015+A1:2020	
LVD	EN IEC62368-1:2020+A11:2020	
Product Family	BS 8300-2:2018	
Physical		
	1ZC	Alarm Plates
Height	86mm	86mm
Width	140mm	86mm
Depth	22mm	12mm
Weight	150g	Total - 180g

Wiring Schematic

