

Wall VAD

ViUV-WV-UL-EU



Unicorn Voice is a unique distributed wall-mounted, panel based voice alarm and fire telephone solution that is compliant to EN54-16.

- Certified to EN 54-23:2013
- Matching VAD
- Synchronised operation
- Low current
- Compatible with Unicorn Voice
- 18V DC to 30 V DC-
- Single UK mounting box
- 1st fix termination plate

Overview

The Wall VAD has been specifically designed to complement the Unicorn Voice PAVA range. It features low current and high performance.

Matching VAD/speaker performance

There are many applications which require the use of VADs (Visual Alarm Devices) to supplement the alarm system to meet the requirements of the Equality Act 2010 and the Building Regulations.

The Wall VAD has specifically been designed to complement the Unicorn Voice range of loudspeakers. It has matching coverage and are fully synchronised so all VADs will be operating together.

Technical Specification

Details	ViUV-WV-UL-EU
VAD specification	
VAD classification	W-2.4-5
Operating voltage	18 TO 30 VDC
Current consumption	12 mA
Frequency range	0.5 HZ
Environmental	
Operating temp	-10°C to 55°C
Humidity range	0 to 80% non-condensing
Ingress Protection	IP21C
MECHANICAL	
Material	Polycarbonate
Colour	White RAL 9016
Dimensons H x W mm	86 x 86
Net Weight	??

Ordering Information

Part Code	Description
Accessories	
ViUV-WV-UL-EU	Ceiling VAD