

Quantec-Pro Corridor Display

Part No. **QP908C**



Overview

- Designed to indicate incoming calls from a Quantec-Pro call system in corridors, staff rooms and nursing stations.
- Includes a high-contrast easy-to-read OLED display that can support place names of up to 24 characters.
- Also features an onboard sounder that can generate multiple standard and HTM specific tones and a series of buttons to accept and/or scroll through current events.
- Shows call type, call location and (depending on the device used to make the call) the User ID or name of the person calling.
- Highest priority calls are shown first with a message saying how many calls are waiting.
- Flash and sounder rates intensify to reflect the urgency of incoming calls.
- Adjustable contrast and volume controls.
- External sounder connection.
- Ergonomically designed and surface mountable.
- Did you know calls can also be shown on smartphones and tablets using our Quantec Surveyor2 App? For details [click here](#).



Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network)
Quiescent current	4.4mA.
Indicators	2 line x 20 characters plus 4 suffix backlit OLED display.



Controls	Accept (A); Scroll Up; Scroll Down. Adjust contrast; Adjust volume; Enable internal/external beeper.
Connections	Net +: Net -
Expansion connections	External sounder connection (current sink to the NET- line rated at 30 V, 30mA, 300 mW dissipation max.)
Onboard Sounder	Yes.
Onboard Infrared Receiver	No.
Product dimensions (mm)	154 W x 125 H x 34 D mm. Surface mounting.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	200g.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.

