

Quantec Infrared Ceiling Receiver Extender (Round Version)

Part No. **QT302RXRS**



Overview

- An unobtrusive white round ceiling mounting infrared extender device.
- Designed to connect to an addressable Quantec infrared receiving device to increase IR coverage.
- Can accept infrared calls from compatible Quantec staff attack transmitters, patient neck/wrist pendants and staff attendance pendants.
- Typically used in bedrooms, corridors, common rooms and any other area requiring infrared coverage.
- Typical 10m line of sight receiving range.
- Up to three QT302RXRS infrared extenders can be used per addressable infrared device.
- Optional QT848/10 locking kit, complete with 10 grubscrews and Allen key, also available.



Technical Specifications

Power requirements	TBC.
Quiescent current	TBC.
Indicators	Red/green confidence LED/diffuser.
Controls	N/A.
Connections	N+: N-; R; G; L+; IR. Wire as a dummy/extender to a Quantec Addressable Call Point or Infrared Ceiling Receiver. See instructions for details.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Sounder	No
Onboard Infrared Receiver	Yes - will accept calls from compatible Quantec infrared transmitters.



Product dimensions (mm)	93mm diameter x 27mm deep. Designed for ceiling mounting only. Base fits 16mm conduit and BESA centres.
Construction & finish	White round plastic.
IP Rating	TBC.
Weight	TBC.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Notes	Optional QT848/10 locking kit, complete with 10 grub screws and Allen key, available.

