

Quantec Addressable Infrared Call Point, Button Reset c/w Iconised Label, Sounder & Remote Socket

Part No. **QT602ERS**



Overview

- A programmable Quantec addressable call point c/w iconised label, infrared receiver, call follower sounder and remote jack socket.
- Includes a Call button, Reset buttons and red/green confidence light.
- Onboard infrared receiver accepts calls from compatible Quantec infrared transmitters.
- Can make up to 7 levels of call - Standard, Ensuite, Help Required, Emergency, Attack, Presence & Attendance (dependent on configuration and ancillary devices used).
- Remote socket allows the connection of optional tail call leads, pressure mats, etc.
- Can be programmed to operate in a multitude of ways using a QT423 configurator.
- Connections provided for ancillary devices such as ceiling pulls, overdoor lights, infrared receivers and more.
- Call follower sounder can be optionally used to inform staff that other calls are waiting when the system is in Night mode (see Technical Specifications for further details).

Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network)
Quiescent current	Less than 3mA.
Alarm current	14mA.
Indicators	Red/green confidence LED.
Controls	Iconised Call button; Iconised Reset button.
Connections	Net +: Net -: R; G; L+; SW; IR; SLV.
Expansion connections	R; G; L+; SW; IR & SLV terminals allow the connection of optional dummy/extender overdoor lights, dummy/extender call points, dummy/extender ceiling pulls and dummy/extender infrared receivers.



Onboard 6.35mm Remote Jack Socket	Yes – for the optional connection of tail call leads/pear pushes, pressure mats and movement detectors.
Onboard Sounder	Yes – can be optionally used for Quantec's Call Follower Sounder feature (if Quantec is in Night mode and the call point is in Presence, the call point will emit a soft tone to signal staff.
Onboard Infrared Receiver	Yes – will accept calls from compatible Quantec infrared transmitter.
Product dimensions (mm)	87 W x 87 H x 33 D mm. Can be mounted on a standard UK 25mm single gang flush or surface back box.
Construction & finish	Plastic.
IP Rating	IP20.
Weight	74g.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.

