

SPECIFICATION SHEET




Email: sales@securiflex.co.uk | Website: www.securiflex.co.uk | Tel: 033 33 44 66 23



SFX/6C-TY3-PE-BLK

6 Core TCCA Type 3 Alarm Black PE

Import / Export Commodity Code 8544492000 / 85444920



Cable Construction	
Cable Construction	6 Cores
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.22
Insulation	
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 ±0.100
Insulation Colour(s)	Red,Black,Blue,Yellow,Green,White
Nylon Rip-Cord	Yellow 210D
Jacket	
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	5.20 ±0.100
Jacket Colour	Black RAL 9005
Sheath Printing	(m)
Reaction to Fire	Fca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	155Ω/km
Rated Temperature (°C)	-20°C to 80°C
Rated Voltage (V)	30V
Insulation Resistance @20°C	>200 MΩ/km
Compliance and Standards	BS4737-3.30:2015,RoHS2 2011/65/EU
Application	For the interconnection of intruder alarm installations.



Every care is taken to ensure all information in this publication is correct. No legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information of this specification without notice. E&OE.
Registered in England & Wales, Company No. 03758330. VAT number:7365084