



SERAGE

NEXT-GEN AI CCTV



16 CHANNEL NVR



No.	Description	No.	Description
1	LINE IN	7	RS485
2	ALARM IN/OUT	8	AUDIO OUT
3	USB PORT	9	VGA OUTPUT (MAIN)
4	PoE INPUTS	10	HDMI OUTPUT (MAIN)
5	POWER SWITCH	11	RESET BUTTON (10SEC)
6	48v DC POWER SUPPLY	12	LAN NETWORK

FEATURES:



NDAA (National Defense Authorization Act) compliant, refers to products that are "safe to use" by government agencies and enterprises.

SR8016NP

Resolution	8MP, 5MP, 3MP, 2MP (1080P) 1.3MP (960P), 1.0MP (720P)
Inputs Bandwidth	112 Mbps
Outputs Bandwidth	96 Mbps
Audio Compression	G.711A;G.711U
Video Compression	H.264/H.264+/H.265/H.265+
Frame rate	4K:45fps 4MP:90fps 2MP:180fps
AI	Yes
Event	MD(Sensitivity Level 1~8)
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	Max 16CH playback
Fisheye	Use WEB CMS,device does not support
Local	UI5.0
Web	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Mobile Application	
Push Notification	Serage AI Yes
Password Reset	
VGA	Factory Reset : Press 10 seconds 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
HDMI 1	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
POE Ports	16*RJ45, 802.3at/af
Ethernet Ports	1 RJ45 10/1000 Base-T
USB Ports	USB2.0*1(front) USB2.0*1+(rear)
Audio Out	1
HDD Bays	1 SATA, up to 10TB
Alarm Input/out	8 in /1out
OSD Language	English/French/Spanish/Portuguese/German Italian/Greek/Danish/Finnish/Russia/Hebrew Turkish/Bulgarian/Arabic/Korean/Japanese Thai/Hindi/Romanian/Dutch/Polish
Dimension (WxDxH)	300X302X54mm
Rack Mount	Shelving required
Input Voltage/Current	DC48V/3.75A PoE Switch :48V
Power Consumption	8W
Operating Temperature	-10°C~+50°C (14°F ~ 122°F)
Humidity	Less than 90%RH