

Ei146e

Optical Smoke Alarm



- Optical sensor - quick response to slow smouldering fires
- Automatic dust compensation
- Mains powered with 9V Alkaline battery back-up
- Easi-fit base for quick and simple installation
- Kitemarked to BS EN14604:2005
- 5 year guarantee



Hallway



Landing



Living Room



Dining Room



Bedroom



Description

The Ei146e Optical Smoke Alarm is a mains powered alarm with a 9V Alkaline battery back-up and contains a proven optical smoke chamber. The alarm features a new modern design and improved optical sensor with sealed insect mesh and automatic dust compensation for reduced false alarms. It is supplied with an easi-fit base to make it quick and simple to install. Compatible with the Ei168RC RadioLINK Base for wireless interconnection

Technical

| | | | |
|---------------------------|---------|------------------------------|--------------------------------------|
| Sensor Type | Optical | Indicators | Green - Power / Red - Alarm or fault |
| Supply Voltage (V) | 230 | Voltage Type | AC |
| Battery Type | PP3 | Power Consumption (W) | 0.75 |

Dimensions & Weights

| | | | |
|-----------------------------|-------|----------------------------|-------|
| Depth (mm) | 60 | Height (mm) | 155 |
| Width (mm) | 155 | Product weight (kg) | 0.346 |
| Packaged weight (kg) | 0.393 | | |

Approvals & Warranty

| | | | |
|--------------------------------|------------------|-----------------|-----------------|
| Certification/Approvals | BS EN 14604:2005 | Warranty | 5 year warranty |
| EAN Number | 5099383010206 | | |

Environmental

| | | | |
|---------------------------|-------|-------------------------------|-----------|
| Humidity Range (%) | 15-95 | Temperature Range (°C) | -10 to 40 |
|---------------------------|-------|-------------------------------|-----------|