

# N40-3

## Exit Sign Frame - 40m Viewing Distance

### Features

- ▶ Complies with BS5266 for 40m viewing and 3 hour duration
- ▶ Range of directional lenses with ISO7010 legends (sold separately)
- ▶ Long-life NiMH battery technology
- ▶ Choice of two fixing angles (ceiling or wall mounted)
- ▶ Robust design.



Frames and lenses sold separately

### Description

The N40-3 is an exit sign frame that can accept a range of directional lenses (sold separately) designed to be viewed from a distance of up to 40 m.

The frame contains an integral long-life NiMH battery which complies with BS 5266 in regards to providing 3 hours of illumination.

The frame can be configured for for fixing either to the ceiling or a wall and twist-fits to Hochiki's standard mounting base, the YBN-R/3(WHT)

### Technical information

Ordering Code	N40-3
Input voltage [VDC]	24 – 40
Input voltage [VAC]	24 – 40
Average power consumption from the line (fully charged battery) [W] <sup>1)</sup>	0.53
Maximum power consumption from the line (31V) [mA] <sup>1)</sup>	23.4
Luminance [cd/m <sup>2</sup> ] (green/white) 1)	11 / 80 (SGR) 8 / 28 (GR)
Luminance active mode [cd/m <sup>2</sup> ] (green/white)	11 / 80 (SGR) 8 / 28 (GR)
Power consumption from the line (31V), panel in sleep mode [mA]	1.3
NiMH battery [V] / [mAh]	1.2/1900
Battery charge time 100% [h]	12/24
Standby time light on [h]	3
Fully charged battery voltage [V]	1.6
Discharged battery voltage	0.8
Dimensions (width x height x depth) [mm] including base	
Wall mounted	322 x 270 x 60
Ceiling mounted	322 x 268 x 99
IP-class <sup>2)</sup>	55
Operation Temperature <sup>3)</sup>	-25 - +40 °C
Material	PC+ABS, fire resistant
Colour	White
Fire class	UL94 V-0
<sup>1)</sup> Default brightness 4 <sup>2)</sup> With separate sealing N-IP-GASKET <sup>3)</sup> Battery life shortens with higher temperature. At temperatures above +30°C battery life shortens to 1/3 with every increase of 10°C. Temperatures <25°C	



For further information visit our website.  
Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.