

SENTINEL PRO SURFACE

EMERGENCY SURFACE DOWNLIGHT OPEN AREA / ESCAPE ROUTE

The Sentinel Pro Surface is the next generation emergency surface offering full flexibility thanks to the interchangeable open area and escape route optic design. Delivering a truly flexible self test product to suit all emergency applications.



Features

- LiFePO4 Battery Technology
- 3 Hours Emergency
- Open Area & Escape Route Optics
- IP65
- Selectable Self Test or Manual Test operation

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
SNP/SS/ST/V2	Sentinel Pro Surface EM NM Area & Escape Selectable ST/M	280lm	280 lm (Open) 230 lm (Escape)	2W	

Product Information

Warranty	5 Years
Emergency Battery Warranty	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Acrylic

Colour Finish	White RAL9003
LED Life Expectancy	102000 Hours
Power Factor	>0.3
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	0°C to +45°C
EM Working Temperature	0°C to 45°C

SENTINEL PRO SURFACE

EMERGENCY SURFACE DOWNLIGHT OPEN AREA / ESCAPE ROUTE

Packaging Information

Dimensions (mm)	L: 155 x W: 155 x D: 46 mm
Product Net Weight (kg)	0.375 kg
Barcode	5055807628228
Box Dimensions (mm)	L:170 x W: 160 x D: 60 mm
Box Gross Weight (kg)	0.449 kg

Units/Outer Carton	20
Outer Carton Barcode	15055807628225
Outer Carton Dimensions (mm)	L:360 x W: 340 x D: 325 mm
Outer Carton Gross Weight (kg)	9.6 kg

