

Ei1000G

SmartLINK Gateway



- Enables remote management of alarm systems and environmental sensors via the HomeLINK Portal
- Transmits data over GSM network (4G roaming SIM)
- Unique House Coding feature
- Easy setup and configuration using dedicated SmartLINK App
- Compatible with SmartLINK, HomeLINK & RadioLINK+ Alarms and Accessories
- HomeLINK software licence included

Description

The Gateway allows remote monitoring of SmartLINK and RadioLINK+ alarm systems and HomeLINK Environmental Sensors via the HomeLINK Portal. The unit is mains powered with built-in rechargeable back up and roaming SIM (4G). It receives information from the alarms and sensors and reports data up to the HomeLINK portal via its GSM connection. For use with the SmartLINK App. HomeLINK software licence included

Technical

RF Frequency (MHz)	868	RF Range (m)	>100 in free air
Indicators	Green - Power / Blue - RF communication / Yellow - GSM communication	Supply Voltage (V)	230
Voltage Type	AC	Battery Type	HHR60AAH
Power Consumption (W)	1.5	Technologies	SmartLINK, HomeLINK

Dimensions & Weights

Depth (mm)	51.5	Height (mm)	152.5
Width (mm)	168.8	Product weight (kg)	0.429
Packaged weight (kg)	0.485		

Approvals & Warranty

Certification/Approvals	Internet of Things (IoT)	Warranty	5 year warranty
EAN Number	5099383010558		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------