

DHI-HY-MRF60-R8

Wireless Interconnected Module



- Compatible with Wisualarm mains powered alarms
- Wireless interconnected with maximum of 24 WisuLink RF devices
- RF mesh interconnected architecture
- Simply plug in module design
- Powered from alarm head

System Overview

The product is an optional add-on wireless interconnected module for the Wisualarm mains-powered alarm units. It enables the Alarm to communicate wirelessly with other WisuLink and WisuLink Pro devices. Up to 24 devices can be interconnected.


Technical Specification

Power Supply	Powered from alarm head
RF Range	Up to 1000 metres in open, interference-free area
RF Visual Indicator	Flashing Red: RF transmission Flashing Blue: Successfully interconnected
RF Frequency	868MHz (-R8) /925 MHz (-R9)
Interconnect	Up to 24 WisuLink RF devices
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	≤95% RH (non condensing)
Color	White
Casing	PC+ABS
Dimensions	53.5 mm × 38.2 mm × 11.7 mm (2.11" × 1.50" × 0.46")
Weight	11.9 g (0.03 lb)
Certifications	CE, UKCA, PSTI, RCM

Ordering Information

Type	Part Number	Description
Wireless Module	DHI-HY-MRF60-R8	Wireless Module
Wireless Module	DHI-HY-MRF60-R9	Wireless Module

Installation



Dimensions (mm/inch)

