PRODUCT DATASHEET · FIRE-RATED CABLE FIXINGS

LINIAN FireClip™

Single-component fire-rated cable clip for single or double cable applications, 4–14 mm.

HUVO
Fluent in fire and security.
huvo.co.uk

AT A GLANCE

Single or double cable
One clip family covers both single and double cable runs.

70% quicker to install
Compared with traditional plug, screw and washer fixings.

18th Edition compliant
Fire-rated cable fixing — safe and compliant to BS 7671.

90 and 120 minute fire resistance
Meets both BSI and DIN classifications.

Smoke emission tested
Tested to the London Underground standard.

Melting point above 1,200 °C
Holds cables in place long after plastic fixings have failed.

Mini trunking alignment
Can be used in line with mini trunking.

FAST AND EASY TO INSTALL

No need for plugs, screws or washers. Drill your hole, slide the clip over the cable and push it into the wall.

1. **Drill a hole in the substrate**
   Ø5 mm for softer substrates and Ø6 mm for harder substrates, to a depth of 30 mm.

2. **Slide the clip over the cable**
   Make sure the cable is seated in the rounded area of the clip.

3. **Compress and push it home**
   Pinch the legs together and push the clip into the hole by hand.

Softer substrates: plaster, plasterboard and similar. **Harder substrates:** concrete, masonry, timber and similar.

PERFORMANCE

24 kg
Safe working load
Single-component design with strength built in.

1,000 h
Salt spray tested
Coated for indoor and outdoor use.

Cable range Ø4 mm – Ø14 mm
Soft-skin, flex and round cables. Singles and doubles.

Available in red, white and black

STANDARDS

FireClip meets all current industry regulations for fire-rated cable support.

BRITISH	EUROPEAN
BS 7671 Amendment 3	DIN 4102-12 E90
BS 7671 18th Edition (2018)	
BS EN 50200 PH120	
BS 8519:2010	

LINIAN FireClip™ range

PART NUMBER	COLOUR	SUITABLE FOR	CABLE OD	CLEAT SIZE*	UOM
4 mm to 6 mm					
1LCR406	Red	Single cable	4–6 mm	CC3	100
1LCW406	White	Single cable	4–6 mm	CC3	100
1LCB406	Black	Single cable	4–6 mm	CC3	100
6 mm to 8 mm					
1LCR608	Red	Single cable	6–8 mm	CC4	100
1LCW608	White	Single cable	6–8 mm	CC4	100
1LCB608	Black	Single cable	6–8 mm	CC4	100
1LCR682	Red	Double cable	6–8 mm	CC4 ×2	100
1LCW682	White	Double cable	6–8 mm	CC4 ×2	100
1LCB682	Black	Double cable	6–8 mm	CC4 ×2	100
9 mm to 11 mm					
1LCR911	Red	Single cable	9–11 mm	CC5	100
1LCW911	White	Single cable	9–11 mm	CC5	100
1LCB911	Black	Single cable	9–11 mm	CC5	100
1LCR9112	Red	Double cable	9–11 mm	CC5 ×2	100
1LCW9112	White	Double cable	9–11 mm	CC5 ×2	100
1LCB9112	Black	Double cable	9–11 mm	CC5 ×2	100
11 mm to 14 mm					
1LCR1114	Red	Single cable	11–14 mm	CC6	100
1LCW1114	White	Single cable	11–14 mm	CC6	100
1LCB1114	Black	Single cable	11–14 mm	CC6	100

HOW TO READ THE CODES

`1LC` — LINIAN FireClip

`R / W / B` — red, white or black

`406 · 608 · 911 · 1114` — cable OD range in mm

`…2` — double cable version (6–8 and 9–11 mm only)

CHOOSING A SIZE

Measure the overall diameter of the cable and pick the band it falls in. The clip should seat the cable in its rounded head without forcing it.

Double cable clips hold two cables of the same size side by side and align with mini trunking.

Need a colour that isn't listed?

FireClip is also made in cream, copper, orange, purple, yellow, brown, green, blue and galvanised finishes. Ask our team for availability and lead times.

* Cleat size may vary — check with the cable manufacturer. All part numbers supplied in boxes of 100. Part numbers as published by LINIAN.