ActiV Conventional Hi-Output 100dB(A) Wall Sounder (shallow base)

Part No. BF430C/CC/SR



Overview

- Third-party certified to EN54-3 (Sounders).
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low)
- Max. Alarm Current at 30Vdc = 6mA.
- Typical Alarm Current at 30Vdc = 4mA.
- IP21C rated.
- Manufactured in the UK by C-TEC.

Technical Specifications

Approvals/certifications	Certified to EN54-3 by the LPCB
Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Indoor areas only.
VAD category & coverage	N/A.
Flash rate & colour	N/A.
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	100dB(A).
Alarm current	Max. @ 30Vdc = 6mA; Typ. @ 30Vdc = 4mA.
Product dimensions (mm)	108mm diameter x 99mm deep

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com

You're Safe with C-TEC

IP Rating	IP21C (Type A).
Weight	215g.
Operating conditions/temperature	-10ºC to +55ºC. Max. 95% RH (Non-condensing).

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: **sales@c-tec.co.uk**
c-tec.com

You're Safe with C-TEC